



Audio Amplifier With Bluetooth, Bluetooth Wireless In-Ceiling Speakers

Price	620.53 Euro
Availability	On order
Shipping time	14 days
Number	1263

Product description

AMP Technical Specifications:

Power Requirements:

AC Supply: AC100-240V, 60/50Hz, 1A | DC Input: DC12-20V @ 5A

Total Quiescent Current: Typical 40mA

Frequency Response: 20Hz to 20KHz(± 3 dB)

Speaker Impedance: 8 ohms - 4 ohms minimum

Output Power(RMS): 2CH*45W

Bluetooth Technical Specifications:

Bluetooth® System: Bluetooth® V4.0

Frequency Range: 2.40GHz-2.4832GHz(ISM Band)

RF Channels: 79 Channels for USA ,Japan, and Europe (Except France)

Transmit Power: +8 dBm MAX, Class 1

Range: Up to 10 Metres

Security: 4-Digit PIN Code

Speaker Technical Specifications:

Rated Power: 30W

Rated impedance: 8Ohm

Frequency Range: 50Hz-20KHz

Sensitivity: 91 \pm 2dB

Hole Size: 185mm

Dimension: ϕ 205*90mm (Diameter * Thickness)

Material: ABS

Speaker Unit: 1"Tweeter, 5.5"Woofer

Temperature & Humidity: Operational Temperature: 32° F - 104° F (0° C - 40° C)

Humidity: 5% - 95% Non-condensing

Storage Temperature: -4° F - 158° F (-20° C - 70° C)

Content:

1"Tweeter, 5.5"Woofer

1pc power adaptor







