Link to the product: https://stair-lighting.com/futc06-floodlight-milight-50w-rgbcct-led-garden-light-p-2654.html

FUTC06 Floodlight MILIGHT - 50W RGB+CCT LED Garden Light

Price	**214.80 Euro**
Availability	**Available**
Shipping time	**14 days**
Number	**2654**
Manufacturer	**Mi.Light**

Product description

Product Name: 50W RGB+CCT LED Garden Light
Model No.: FUTC06
Power: 50W
Input Voltage: AC100~240V 50/60Hz
Working Temperature: -20-60°C
Color Temperature: 2700K~6500K
Luminous Flux: 4000LM
Luminous Efficiency: 80LM/W
CRI: >80
PF: >0.9
Lifespan: 50000 hours
Beam Angle: 25°
Illumination distance: >15m
IP Rate: IP65
RF: 2.4GHz
Control Distance: 30m

50W RGB+CCT LED Garden Light

2.4GHz Remote control & APP control, Support Third Party Voice Control, Automatic commands transmitting function, Auto-synchronization

16 million colors change | CCT Adjustable | Dimmable Saturation control | IP65 waterproof rate

IP65

2.4GHz RF Remote Control

The lamp is controlled by 2.4GHz wireless remote; Control distance is within 30m

IP65

Compatible with

FUT089 FUT088 FUT092 FUT095 FUT096 B8 B4/T4 B3/T3 B0 WL-Box1

Support Smart phone APP control and third party voice control

It need 2.4GHz gateway(WL-Box1) for smart phone control or third party voice control

WORKS WITH
amazon alexa

works with the
Google Assistant

2.4GHz Gateway
WL-Box1

16 Million colors / Saturation control

Brightness adjustable & Color temperature adjustable

Brightness adjustable, Adjust the color temperature from 2700-6500K,
make the light you want

IP65 Waterproof

Professional waterproof technology,
high performance waterproof

Signal transmitting

One lighting fixture can transmit the signals from
the remote control to another lighting fixture
within 30m, as long as there is a lighting fixture
within 30m, the remote control distance can be
limitless.

Modes synchronization

Different lighting fixture can work synchronously
when they are started at different times, controlled
by the same remote, under same dynamic mode
and within 30m distance.

Signal transmitting &
Modes synchronization

Signal transmitting &
Modes synchronization

Distance 30m

Distance 30m

Distance 30m

High lumen LED Chips

Low power consumption
and luminance decrease;
Bright color and high brightness

Optical Lens

Anti-dazzling optical lens; diverging
light scientifically. Symmetrical and
bright light ray

IP65

High efficiency heat dissipation

Integrative Aluminum design; Inserted thermal conduction, Protect light source lifespan

Waterproof plug

Copper nickel plating material, Waterproof and dustproof, never rusting

220mm

47.5mm

265mm

310.5mm

IP65