

Link to the product: <https://stair-lighting.com/led-strip-5050-300-diod5m-waterproof-blue-p-491.html>

## LED STRIP 5050 300 diod/5m waterproof - blue

Price	<b>35.70 Euro</b>
Availability	<b>Available</b>
Shipping time	<b>48 hours</b>
Number	<b>491</b>
Manufacturer	<b>RESTAN</b>

### Product description

LED strips - a modern solution capable of lighting advertising , furniture, shop windows and decorative lighting and utility rooms. LED strips offer minimal power consumption while providing high performance light. The small size combined with flexibility allows its use PCB where other light sources do not permit their assembly , or is difficult. The use of LED strip leaves only limited by your imagination .

Products offered by RESTAN feature - the highest quality of workmanship , found thanks to the recognition of the various embodiments where the investor require reliability and durability of LED lighting . LED strip production is monitored at every stage - from purchasing the highest quality components in the packaging process . This attention to detail ensures its reliable operation for many years.

Components for each tape led to : the highest quality LEDs , PCB laminate tested , selected resistors . Yes precise selection of components allows you to ensure uninterrupted operation LED strips for many years. Each roll of tape led a process of thorough quality control , ensuring our customers receive the highest quality merchandise. Highest quality LED strip is confirmed by a 2 year warranty.

#### SPECIFICATIONS

Dimensions	Width 8 x thickness of 2.9 [mm]
Power supply	12 V DC
Power	6A/5m (1,2A/m)
Consumption	
Power1	72W/5m (14,4W/m)
Type of applied LED	SMD 5050
LED qty	300
LED viewing angle 120 degree	
Ability to cut LED strip	marked cutting line every 3 LEDs
Mouting	a flexible laminate (white)
MOuting	M adhesive tape placed at mid-life
Life	30 000 - 50 000 hours

#### SPECYFIKACJA TECHNICZNA

Wymiary	szer. 8 x grubość 2,9 [mm]
Napięcie zasilania	12 V DC
Pobór prądu	6A/5m (1,2A/m)

Pobór mocy	72W/5m (14,4 W/m)
Typ zastosowanej diody	SMD 5050
Ilość LED	300
Kąt świecenia diody	120 stopni
Możliwość cięcia taśmy LED	zaznaczona linia cięcia co 3 diody
Podłoże	elastyczny laminat (kolor biały)
Sposób montażu	samoprzylepna taśma 3M umieszczona na laminacie
Żywotność	30 000 - 50 000 godzin

