

Link to the product: <https://stair-lighting.com/led-strip-professional-ip65-rgb-p-53.html>

LED strip professional IP65 -RGB

Price	61.22 Euro
-------	-------------------

Availability	Available
--------------	------------------

Shipping time	5 days
---------------	---------------

Number	57
--------	-----------

Manufacturer	RESTAN
--------------	---------------

Product description

LED strips - a modern solution capable of lighting advertising, furniture, shop windows and decorative lighting and utility rooms. LED strips offer minimal power consumption while providing high performance light. The small size combined with flexibility allows its use PCB where other light sources do not permit their assembly, or is difficult. The use of LED strip leaves only limited by your imagination.

Products offered by RESTAN feature - the highest quality of workmanship, found thanks to the recognition of the various embodiments where the investor require reliability and durability of LED lighting. LED strip production is monitored at every stage - from purchasing the highest quality components in the packaging process. This attention to detail ensures its reliable operation for many years.

Components for each tape led to: the highest quality LEDs, PCB laminate tested, selected resistors. Yes precise selection of components allows you to ensure uninterrupted operation LED strips for many years. Each roll of tape led a process of thorough quality control, ensuring our customers receive the highest quality merchandise. Highest quality LED strip is confirmed by a 2 year warranty.

Light color: RGB (multicolor)

Luminous flux (meter): 33 lm red-green-blue-83 lm 38 lm

Luminous flux (5 meters): 167 lm red-green-blue-1m 416 lm 188

Number of LEDs (meter): 30

Number of LEDs (roll 5 meters) 150

Voltage: 12V DC

Power consumption (meter): 6 ~ 7.2 W

Power Consumption (roll 5 meters): 30 ~ 36W

Current consumption (meter): 0.5 ~ 0.6 A

Current consumption (roll 5 meters): 2.5 ~ 3A

LED type: SMD5060 (3xCHIP)

Viewing angle: 120 °

Section cut: 10cm

Backing: Flexible copper PCB laminate

Ground color: white

Dimensions (W x H) 10 x 2.5 (mm)

Life: 35 000 hours

Degree of protection IP: lack of protective coating

Warm-up Time to 60% of: 1 s

Number of cycles on / off: 50000

Stream factor Świetenego after 30 000 h light: 30%

Starting time: 1.1 sec

Color rendering index: ? 75

Lamp power factor: ? 0.5

Cooperation with dimmer: only with dimmers PWM

