

Link to the product: <https://stair-lighting.com/led-strips-5m-professional-ip65-blue-p-905.html>

LED strips 5m professional IP65 - blue

Price	69.85 Euro
Availability	Available
Shipping time	4 days
Number	905
Manufacturer	RESTAN

Product description

LED strips - a modern solution capable of lighting advertising , furniture, shop windows and decorative lighting and utility rooms. LED strips offer minimal power consumption while providing high performance light. The small size combined with flexibility allows its use PCB where other light sources do not permit their assembly , or is difficult. The use of LED strip leaves only limited by your imagination .

Products offered by RESTAN feature - the highest quality of workmanship , found thanks to the recognition of the various embodiments where the investor require reliability and durability of LED lighting . LED strip production is monitored at every stage - from purchasing the highest quality components in the packaging process . This attention to detail ensures its reliable operation for many years.

Components for each tape led to : the highest quality LEDs , PCB laminate tested , selected resistors . Yes precise selection of components allows you to ensure uninterrupted operation LED strips for many years. Each roll of tape led a process of thorough quality control , ensuring our customers receive the highest quality merchandise. Highest quality LED strip is confirmed by a 2 year warranty.

Number of LEDs (meter) : 60
Number of LEDs (roll 5 meters) - 300
Voltage: 12V DC
Power consumption (meter) : 12 ~ 14.4 in
Power Consumption (roll 5 meters) : 60 ~ 72W
Current consumption (meter) : 1 ~ 1.2 A
Current consumption (roll 5 meters) : 5 ~ 6A
LED type : SMD5050
Viewing angle: 120 °
Section Cutting : 5cm
Backing: Flexible copper PCB laminate
Ground color : white
Dimensions (W x H) - 10 x 2.5 (mm)
Life : 35 000 hours
Degree of protection IP: lack of protective coating
Warm-up Time to 60% of : 1 s
Number of cycles on / off : 50000
Stream factor światlenego after 30 000 h light : 30%
Starting time : 1.1 sec
Color rendering index : ≥ 75
Lamp power factor : ≥ 0.5
Cooperation with dimmer : only with dimmers PWM

