

Link to the product: https://stair-lighting.com/plakin-duo-silver-anodized-profile-led-led-channel-led-extructions-a04106a-p-2941.html



PLAKIN-DUO silver anodized profile LED, led channel, led extructions A04106A

Price	39.78 Euro
Availability	Available
Shipping time	4 days
Number	2941
Manufacturer	KLUS

Product description

Important Information

The purchase a piece in the store means the purchase 1 linear meter of the profile or cover

If you want to buy a profile that has a length of 2 meters you have to buy 2 pieces, 3 meters you have to buy 3 pieces, and the multitude of quantity when ordering.

The total length of the aluminum profile or the panel to the profile - is the total quantity of the piece number that was bought in the store.

The choice of the appropriate shipping method will take place at the end of the order process. The details of the shipping method and packaging of the aluminum profiles you will find here (click in the link)

Profile for the construction of wall fixtures (sconce fixtures), with an option of simultaneous up and down lighting. It has integrated functions: fitting of LEDs and protecting them with a cover (diffuser), surface mounting, as well as an option of installation of power supply and other electronic components, profiles length 100, 200 cm.

The product you have selected contains only - aluminum profile - does not include the accessories located in the Accessories

Additional accessories like covers, end caps, electricity conductive end cap, mounting bracket, fasteners, mounting springs, proximity switch, micro switch, mounting system and others are available under "Accessories".

If you are interested in longer lengths than one meter, write to us we will quote the delivery cost to you. Transport companies expect additional charges for long shipments.

For each country is different maximum length of the profile that we can send. It does not depend on us only by courier. We also do service cutting aluminum profiles to the indicated size - write or call get comprehensive information.

- Hidden light source
- Up/down lighting
- Space for power supply and electronic components
- · Easy maintenance

APPLICATION

· - decorative lighting



MOUNTING

- - to the surface, using a dedicated mounting track and properly selected screws
- - can be easily connected into runs and systems

ADDITIONAL INFORMATION

- - various coatings can be applied to the surface of the profile veneer, plaster, paint
- - the power supply can be secured inside the profile using dedicated accessories
- - standard lengths of profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- - when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service