




Części niezbędne do użycia zawieszki DP

Głowica (C)

Podkładka tworzywowa (B)



Śruba tworzywowa (A)




Elementy niezbędne przy czynnościach montażowych:

- wiertarka
- klucz ampulowy


UWAGA! Lista produktów, z którymi współpracują wybrane akcesoria dostępna jest na stronie

1. Nawierć otwór o średnicy 5 mm w wybranym profilu.




Fi 5 mm


2. Sfrezuj otwór tak, by pasował do niego łeb śruby tworzywowej.




3. Zamontuj śrubę tworzywową (A), od góry nałóż na nią złożone razem: podkładkę tworzywową (B) i głowicę (C).




4. Wklej taśmy LED.




5. Zainstaluj pręt w mocowniku głowicy. Zablokuj pręt, dokręcając docisk w głowicy kluczem ampulowym.



6. Zawieś oprawę na wybranym systemie.







Parts needed to mount the DP fastener

Head (C)

Plastic base (B)



Plastic screw (A)




Tools needed for mounting:

- drill
- Allen wrench


NOTE! A list of products corresponding with the selected accessories is available

1. Drill a hole with a diameter of 5 mm in the selected extrusion.




Fi 5 mm


2. Bevel the hole so that the plastic screw head fits in.




3. Mount the plastic screw (A), on the top of it mount the assembled plastic base (B) and head (C).



4. Mount the LED strip.



5. Insert the rod into the mounting bracket of the head. Block the rod by tightening the pressure screw in the head with the Allen wrench.



6. Suspend the lighting fixture using a chosen system.

