

Link to the product: <https://stair-lighting.com/power-supply-voltage-hlg-120-p-244.html>

## Power supply voltage HLG-120



Price	<b>97.33 Euro</b>
Availability	<b>On order</b>
Number	<b>244</b>
Manufacturer	<b>MEAN WELL</b>

### Product description

Power packs of HLG series are intended outdoor LED applications. about the step IP 65 protections have the metal casing ~ IP 67. They are equipped with the active PFC filter, they are meeting the sternest EMC norms. the HLG- 120 Model is appearing also in the version with the increased scope of input voltages 90 ~ 305 VAC - marking with letter H in the name (HLG- 120 H-x). Merlon - IP 67, potentiometers are missing to the regulation of the tension and the output current and - IP 65, 2 available potentiometers built in from the outside to the regulation of the tension and the output current in the scope c 50 ~ 100 % In

B - IP 67, potentiometers are missing to the regulation of the tension and the electricity, additional pair of wires for the connection: - of resistor from 10 kΩ to 100 of kΩ corresponding to limiting the current in the scope from 10 ~ 100 % In (leaving the pair of wires obtuse is tantamount to placing max.. of power-driven productivity of the power pack in scope 102 ~ 108 % In - of outside tension signal (dimmer) from scope 1 ~ 10 VDC what enables the fluid adjustment of the power-driven productivity of the power pack in scope 10 ~ 100 % In - of outside PWM digital signal, with which through the change of the rate of filling up from scope 10 ~ 100 % it is possible smoothly to adjust the power-driven productivity of the power pack in scope 10 ~ 100 % IN C - the HLG- power pack of 120 H isn't appearing in the C version