

Link to the product: <https://stair-lighting.com/profiel-led-pds-t-p-2568.html>

Profiel LED PDS-T

Price	8.59 Euro
Availability	Available
Shipping time	5 days
Number	2565
Manufacturer	KLUS

Product description

Important Information

The purchase a piece in the store means the purchase 1 linear meter of the profile or cover

If you want to buy a profile that has a length of 2 meters you have to buy 2 pieces, 3 meters you have to buy 3 pieces, and the multitude of quantity when ordering.

The total length of the aluminum profile or the panel to the profile - is the total quantity of the piece number that was bought in the store.

The choice of the appropriate shipping method will take place at the end of the order process.

[The details of the shipping method and packaging of the aluminum profiles you will find here \(click in the link\)](#)

The product you have selected contains only - aluminum profile - does not include the accessories located in the Accessories tab.

Additional accessories like covers, end caps, electricity conductive end cap, mounting bracket, fasteners, mounting springs, proximity switch, micro switch, mounting system and others are available under "Accessories".

If you are interested in longer lengths than one meter, write to us we will quote the delivery cost to you. Transport companies expect additional charges for long shipments.

For each country is different maximum length of the profile that we can send. It does not depend on us only by courier.

We also do service cutting aluminum profiles to the indicated size - write or call get comprehensive information.

The profile height is within the thickness of one 12.5 mm drywall board

The PDS-T profile is compatible with the PDS-ZM-PLUS profile, which enables effective transitioning of recessed lighting fixtures into suspended fixtures (ceilings at different levels, mezzanines)

The profile is compatible with the 8-KLIK LED tape system (easy maintenance and quick mounting of IP65 LED tapes)

The cover is cut flush with the profile

Line of light

Application

- for creating simple, polygonal lighting fixtures, recessed in drywall, flush with their surface, without visible aluminum elements.

Assembly

- the profile is mounted to the drywall with screws.

Additional information

- the profile is adapted to LED tapes with a maximum width of 10 mm,

- the profile is equipped with a small "ZM" lock, thanks to which it can be connected using ZM connectors and thus create various shapes.













