


Link to the product: <https://stair-lighting.com/profil-channel-led-extrusions-fasko-a04323-klus-p-2935.html>



Profil, channel, LED extrusions FASKO - A04323 klus

Price	23.87 Euro
Availability	Available
Shipping time	5 days
Number	2935
Manufacturer	KLUS

Product description

Important Information

The purchase a piece in the store means the purchase 1 linear meter of the profile or cover

If you want to buy a profile that has a length of 2 meters you have to buy 2 pieces, 3 meters you have to buy 3 pieces, and the multitude of quantity when ordering.

The total length of the aluminum profile or the panel to the profile - is the total quantity of the piece number that was bought in the store.

The choice of the appropriate shipping method will take place at the end of the order process.

[The details of the shipping method and packaging of the aluminum profiles you will find here \(click in the link\)](#)

Profil LED GIP - Anodized aluminum lens cover 1m ((accessories sold separately - accessories in the section))

The product you have selected contains only - aluminum profile - does not include the accessories located in the Accessories tab.

Additional accessories like covers, end caps, electricity conductive end cap, mounting bracket, fasteners, mounting springs, proximity switch, micro switch, mounting system and others are available under "Accessories".

If you are interested in longer lengths than one meter, write to us we will quote the delivery cost to you. Transport companies expect additional charges for long shipments.

For each country is different maximum length of the profile that we can send. It does not depend on us only by courier.

We also do service cutting aluminum profiles to the indicated size - write or call get comprehensive information.

- For installation on facades
- Illuminated rustication of the facade
- Possibility of installing sealed 8K series LED strips
- Line of light flush with the surface
- Non visible aluminum elements

APPLICATION

- - decorative lighting

MOUNTING

- - in the thermal insulation layer of the building facade, using assembly adhesives

ADDITIONAL INFORMATION

- - the use of a dedicated mounting insert allows the installation of two LED strips in the 8K sleeve

- - standard lengths of profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- - when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at