

Link to the product: https://stair-lighting.com/profil-channel-led-extrusions-pok-us-white-ral9010-p-2831.html



Profil, channel, LED extrusions POK-US white (RAL9010)

Price	54.10 Euro
Availability	Available
Shipping time	5 days
Number	2831
Manufacturer	KLUS

Product description

Important Information

The purchase a piece in the store means the purchase 1 linear meter of the profile or cover

If you want to buy a profile that has a length of 2 meters you have to buy 2 pieces, 3 meters you have to buy 3 pieces, and the multitude of quantity when ordering.

The total length of the aluminum profile or the panel to the profile - is the total quantity of the piece number that was bought in the store.

The choice of the appropriate shipping method will take place at the end of the order process. The details of the shipping method and packaging of the aluminum profiles you will find here (click in the link)

Profil LED GIP - Anodized aluminum lens cover 1m ((accessories sold separately - accessories in the section))

The product you have selected contains only - aluminum profile - does not include the accessories located in the Accessories tab.

Additional accessories like covers, end caps, electricity conductive end cap, mounting bracket, fasteners, mounting springs, proximity switch, micro switch, mounting system and others are available under "Accessories".

If you are interested in longer lengths than one meter, write to us we will quote the delivery cost to you. Transport companies expect additional charges for long shipments.

For each country is different maximum length of the profile that we can send. It does not depend on us only by courier. We also do service cutting aluminum profiles to the indicated size - write or call get comprehensive information.

- Linear gallery, stage or exhibition lighting
- The lighting fixture integrates with the mounting surface
- Hidden light source
- Lighting angle: 50 Degrees
- Mounting to 16 mm | 0.63" drywall
- Stable moutning to a suspended ceiling

APPLICATION

• - decorative lighting and functional

MOUNTING

- - in drywall, with screws
- - can be easily connected into runs

ADDITIONAL INFORMATION



