

Link to the product: <https://stair-lighting.com/profil-channel-led-siler-white-p-2806.html>

Profil, channel LED SILER white



Price	9.23 Euro
Availability	Available
Shipping time	3 days
Number	2806
Manufacturer	KLUS

Product description

Important Information

The purchase a piece in the store means the purchase 1 linear meter of the profile or cover

If you want to buy a profile that has a length of 2 meters you have to buy 2 pieces, 3 meters you have to buy 3 pieces, and the multitude of quantity when ordering.

The total length of the aluminum profile or the panel to the profile - is the total quantity of the piece number that was bought in the store.

The choice of the appropriate shipping method will take place at the end of the order process.

[The details of the shipping method and packaging of the aluminum profiles you will find here \(click in the link\)](#)

Not anodized aluminum profile

The product you have selected contains only - aluminum profile - does not include the accessories located in the Accessories tab.

Additional accessories like covers, end caps, electricity conductive end cap, mounting bracket, fasteners, mounting springs, proximity switch, micro switch, mounting system and others are available under "Accessories".

If you are interested in longer lengths than one meter, write to us we will quote the delivery cost to you. Transport companies expect additional charges for long shipments.

For each country is different maximum length of the profile that we can send. It does not depend on us only by courier.

We also do service cutting aluminum profiles to the indicated size - write or call get comprehensive information.

Profile uniwersalne do montażu na powierzchni, wbudowania lub podwieszenia /
Universalprofile zur Aufputz, Unterputzmontage oder zum Abhängen

SILER

REF. B9325




Może pomieścić taśmy LED o szerokości do 14 mm.
Możliwość uzyskania oprawy wodoszczelnej.

PRZEZNACZENIE PRODUKTU:

- do budowy opraw wodoszczelnych w zastosowaniach zewnętrznych. Na przykład do podświetleń elementów elewacji budynków, elementów małej architektury, do oświetlenia wjazdów garażowych.

MONTAŻ:

- za pośrednictwem klejów montażowych, profesjonalnych taśm dwustronnie przyklepnych,
- za pośrednictwem mocowników 45.



Kann Led-Streifen bis 14 mm breit aufnehmen.
Kann wasserdicht gemacht werden.

ANWENDUNG

- zur Montage von wasserdichten Leuchten für den Einsatz draußen. Z.B. zur Hervorhebung von Fassadenelementen von Gebäuden, Stadtmöbel, für die Beleuchtung von Garageneinfahrten

MONTAGE

- mit Montageklebern, professionellen doppelseitigen Klebebändern
- mit Befestigungsclips 45

profil / Profil

długość / Länge	szerokość LED / LED-Breite	wykończenie powierzchni / Oberfläche	numer artykułu / Artikelnummer
1 m	14 mm	● Srebrny anodowany / Silber eloxiert	B9325ANODA_1
2 m			B9325ANODA_2
3 m			B9325ANODA_3

akcesoria / Zubehör


osłony mleczne / opale Abdeckungen	zawieszki / Befestigungen	zestawy mocowań / Befestigungssätze	inne akcesoria / sonstiges Zubehör
SILER 17039	PUSZ-LIN-MR 42258	RG-1 42647	DŁAWNICA 8.8X1.2 / KABELVERSCHRAU- BUNG 8.8X1.2 00802
zaślepki szare / graue Endkappen	PUSZ-PRET-MR 42252	RG-1 42648	
SILER 24236	DP 00644		
zaślepki HQ / HQ Endkappen	DP-MOC 00645		
SILER-HQ 42640	DP-MOC-ZO 00646		
	DP-MOC-ZZ 00647		
	DP-ZO 00649		
	DP-ZZ 00651		
mocowniki / Befestigungsclips			
45-STN 24144	sprężyny mocujące / Befestigungsfedern		
45 24265	PDS 00800		
45 24262			



Universal Extrusions for surface mount, recessed or suspended applications /
Perfiles universales para aplicaciones de montaje en superficie, empotradas o suspendidas

SILER

REF. B9325



Will accommodate LEDS up to (0.55" / 14 mm) wide.

APPLICATION

- for the construction of watertight lighting fixtures, for external use.
- to highlight elements of building facades, elements of street furniture, to illuminate garage driveways, etc.

ASSEMBLY

- with fixing glues, professional double-sided adhesive tapes.
- with mounting brackets - 45.

ADDITIONAL INFORMATION

- can be equipped with frosted covers and aluminum-colored plastic end caps.



Sus dimensiones permiten colocar en ella una tira LED de (0.55" / 14 mm) .

APLICACIÓN

- para la construcción de luminarias impermeable, para uso externo.
- para resaltar elementos de fachadas de edificios, elementos de mobiliario urbano, iluminar caminos de garaje, etc.

MONTAJE

- con colas de fijación, cintas adhesivas profesionales de doble cara.
- con soportes de montaje - 45.

INFORMACIÓN ADICIONAL

- equipado con difusores escarchadas y tapas de plástico color aluminio.

extrusion / perfil

length / longitud	space for LED strip / espacio para tira de LED	surface finish / terminado de superficie	reference number / número de artículo
39.4" / 1 m			B9325ANODA_1
78.7" / 2 m	0.55" / 14 mm	● Silver anodized / Ánodo de plata	B9325ANODA_2
118" / 3 m			B9325ANODA_3

accessories / accesorios

frosted covers / difusores escarchadas	fasteners / soportes	mounting sets / sets de montaje	other accessories / otros accesorios
SILER 17039	PUSZ-LIN-MR 42258	RG-1 42647	8.8x1.2 GLAND / GLÁNDULA 00802
	PUSZ-PRET-MR 42252	RG-1 42648	
grey end caps / tapas finales gris	DP 00644		
SILER 24236	DP-MOC 00645		
	DP-MOC-ZO 00646		
HQ end caps / tapas finales HQ	DP-MOC-ZZ 00647		
SILER-HQ 42634	DP-ZO 00649		
	DP-ZZ 00651		
mounting brackets / soporte de montaje	mounting springs / resortes de montaje		
45-STN 24144	PDS 00800		
45 24265			
45 24262			



The Siler profile falls into the group of basic profiles. Its design is similar to the PDS-ALU profile, although it has a slightly larger width, so you can put in it LED strips with a width of 10 mm in the silicone sleeve.

The cross-section of the Siler profile results from the shape of the channel section. The internal dimension of the width of the plane to which the strips are glued is approx. 16.6 mm. The depth of the profile is 11 mm.

The side elements of the product from the outside are equipped with slots, allowing the use of "45" mountings.

The siler profile is designed with a special cover of the same name in the milk version and a corresponding plug with aluminum fixing elements made of ABS plastic.

The profile has a very versatile application, creates a distinct, stylish line of light.

