

Link to the product: <https://stair-lighting.com/profil-glaza-ll-black-p-2597.html>

Profil GLAZA-LL - black

Price	12.25 Euro
Availability	Available
Shipping time	3 days
Number	2596
Manufacturer	KLUS

Product description

Important Information

The purchase a piece in the store means the purchase 1 linear meter of the profile or cover

If you want to buy a profile that has a length of 2 meters you have to buy 2 pieces, 3 meters you have to buy 3 pieces, and the multitude of quantity when ordering.

The total length of the aluminum profile or the panel to the profile - is the total quantity of the piece number that was bought in the store.

The choice of the appropriate shipping method will take place at the end of the order process.

[The details of the shipping method and packaging of the aluminum profiles you will find here \(click in the link\)](#)

Profil LED GIP - Anodized aluminum lens cover 1m ((accessories sold separately - accessories in the section))

The product you have selected contains only - aluminum profile - does not include the accessories located in the Accessories tab.

Additional accessories like covers, end caps, electricity conductive end cap, mounting bracket, fasteners, mounting springs, proximity switch, micro switch, mounting system and others are available under "Accessories".

If you are interested in longer lengths than one meter, write to us we will quote the delivery cost to you. Transport companies expect additional charges for long shipments.

For each country is different maximum length of the profile that we can send. It does not depend on us only by courier.

We also do service cutting aluminum profiles to the indicated size - write or call get comprehensive information.

Technical specification

Application

- decorative lighting.

Assembly

- suspended using dedicated accessories,
- to the surface with bolts.

Additional information

- line of light obtainable with the LIGER-22 cover and a LED tape with at least 120 LEDs per meter,
- GLAZA-LL profile is intended for two or one 10 mm wide LED tape,
- two tapes provide uniform illumination of the cover over its entire width,
- LED tape gluing width in the profile is 21 mm,
- cover and profile are equally long,
- broken line of light possible with the MP-22 masking cover,
- can be combined into strings using ZM connectors, small locks inside the profile,

- linear fixture with IP67 protection possible,
- IP67 possible with LIGER-22, MUN-22 and HS-22 covers.

Profile bending

Minimum radius for a bent fixture shining inwards

400 mm

Minimum radius for a bent fixture shining outwards

300 mm

- minimum radius - bending radius which when exceeded causes destruction (deformation, bending or lack of compatibility with other accessories, e.g. covers, end caps, etc.) of the profile,
- internal radius - refers to the extrusion bent so that the cover is facing the inside of the arch,
- external radius - refers to the extrusion bent so that the cover is facing the outside of the arch,
- irregular curves are possible after consultation and individual quotation,
- when bending anodized extrusions, one should be aware of cracking of the anode coating (which may be more or less visible depending on the radius).









