Data current as of: 29-03-2024 08:35

Link to the product: https://stair-lighting.com/profile-led-pds-4-k-nu-pro-7k-alu-ano-p-66.html



Profile LED PDS-4-K - NU-PRO 7K ALU ANO

Price	**6.57 Euro**
Availability	**Available**
Shipping time	**3 days**
Number	**66**
Manufacturer	**KLUS**

Product description

Important Information

The purchase a piece in the store means the purchase 1 linear meter of the profile or cover

If you want to buy a profile that has a length of 2 meters you have to buy 2 pieces, 3 meters you have to buy 3 pieces, and the multitude of quantity when ordering.

The total length of the aluminum profile or the panel to the profile - is the total quantity of the piece number that was bought in the store.

The choice of the appropriate shipping method will take place at the end of the order process.
The details of the shipping method and packaging of the aluminum profiles you will find here (click in the link)


The product you have selected contains only - aluminum profile - does not include the accessories located in the Accessories tab.
Additional accessories like covers, end caps, electricity conductive end cap, mounting bracket, fasteners, mounting springs, proximity switch, micro switch, mounting system and others are available under "Accessories".


If you are interested in longer lengths than one meter, write to us we will quote the delivery cost to you. Transport companies expect additional charges for long shipments.
For each country is different maximum length of the profile that we can send. It does not depend on us only by courier.
We also do service cutting aluminum profiles to the indicated size - write or call get comprehensive information.

Profile do wbudowania /
Profile für Einbaumontage

PDS-4-K

REF. B3776





Możliwość uzyskania linii światła.
Maskowanie krawędzi wpustu.

PRZEZNACZENIE PRODUKTU:
- budowa opraw wbudowanych, głównie do stosowania we wnętrzach np: podświetlenie mebli.

MONTAŻ:
- za pośrednictwem klejów montażowych i profesjonalnych taśm dwustronnie przylepnych.

Lichtlinienfähig.
Abdecken des Nutrandes.

ANWENDUNG
- für eingebaute Leuchten, hauptsächlich in Innenräumen z.B.: Möbelbeleuchtung

MONTAGE
- mit Montageklebern und professionellen doppelseitigen Klebebändern

profil / Profil

długość / Länge	szerokość LED / LED-Breite	wykończenie powierzchni / Oberfläche	numer artykułu / Artikelnummer
1 m	11 mm	Srebrny anodowany / Silber eloxiert	**B3776ANODA_1**
2 m			**B3776ANODA_2**
3 m			**B3776ANODA_3**

akcesoria / Zubehör

osłony mleczne / opale Abdeckungen	
KA	**17035**
KA-COM	**17121**
HS	**1369**
LIGER	**17037**

osłony czarne / schwarze Abdeckungen	
LIGER	**17040**

osłony przezroczyste / transparente Abdeckungen	
KA	**17036**
KA-COM	**17122**
HS	**1370**

zaślepki szare / graue Endkappen	
PDS-4-K	**1438**
PDS-4-K-OTW	**1447**
PDS-4-K-MW	**00032**
PDS-4-K-OTW-MW	**00309**

zaślepki białe / weisse Endkappen	
PDS-4-K	**20005**
PDS-4-K-OTW	**21005**
PDS-4-K-OTW-MW	**22005**

zaślepki metalizowane / metallisierte Endkappen	
PDS-4-K	**24063**


inne akcesoria / sonstiges Zubehör	
DŁAWNICA 8.8X1.2 / KABELVERSCHRAUBUNG 8.8X1.2	**00802**


generated by the shopGold

Recessed extrusions /
Perfiles empotrados

PDS-4-K

REF. B3776





Possible to obtain a line of light.
Masking the channel edge.

APPLICATION
- construction of recessed lighting fixtures.
- furniture lighting.

ASSEMBLY
- with mounting adhesive.

Capacidad de obtener una línea de luz.
Enmascarando el borde del canal.

APLICACIÓN
- construcción de luminarias empotrados.
- iluminación de muebles.

MONTAJE
- con adhesivo de montaje.

extrusion / perfil

length / longitud	space for LED strip / espacio para tira de LED	surface finish / terminado de superficie	reference number / número de artículo
39.4" / 1 m	0.43" / 11 mm	Silver anodized / Ánodo de plata	B3776ANODA_1
78.7" / 2 m			B3776ANODA_2
118" / 3 m			B3776ANODA_3

accessories / accesorios

frosted covers / difusores escarchadas	
KA	17035
KA-COM	17121
HS	1369
LIGER	17037

black covers / difusores negro	
LIGER	17040

clear covers / difusores transparentes	
KA	17036
KA-COM	17122
HS	1370

grey end caps / tapas finales gris	
PDS-4-K	1438
PDS-4-K-OTW	1447
PDS-4-K-MW	00032
PDS-4-K-OTW-MW	00309

white end caps / tapas finales blanco	
PDS-4-K	20005
PDS-4-K-OTW	21005
PDS-4-K-OTW-MW	22005

metalized end caps / tapas finales metalizados	
PDS-4-K	24063

other accessories / otros accesorios	
8.8x1.2 GLAND / GLÁNDULA	00802

generated by the shopGold

Profile PDS4-K was designed for letting him into the ground. Profile made of high-grade aluminum, which has been subjected to double anodizing, so that the profile is resistant to corrosion processes and all kinds of mechanical damage. It is designed to tapes and strips whose width is not greater than 10.8 mm with the LED light sources.

Typically, this profile is used to lighting and illumination (depending on the power used in the LED bulbs), for indoor applications - you can place it in the channels, including the boards of furniture, plates of cardboard, plaster and even in planes of walls, for outdoor applications - in this case it is possible to obtain IP 67 waterproof, so you will not need to worry that the profile is damaged by weathering or UV radiation. After obtaining high tightness profile can be used to illuminate the exterior architectural elements.

Small size profile can be hidden in the walls of the fitting furniture with small cross-sections, a special flange allows a perfect hide unsightly edge of the channel, or cavities present in the plane of the plates, cardboard - plaster and many others.

Installation profile should take place in a specially prepared for this purpose recess. For installation it is recommended to use double-sided tape or adhesive mounting.

If you apply a very densely spaced LEDs and milky cover HS or LIGER is possible to obtain a uniform line of light.

The LEDs should override a special cover, making them more functional. You can choose the cover type K, KA-BIS, HS (optional cover is milky and transparent), LIGER (matte cover) or the classic transparent focusing S, which allows for angle and amounting to exactly 10 degrees.

The material from which were made to cover polycarbonate, a shield HS is certified to guarantee resistance to rain, sun and other weather factors and flammability.

Profile PDS4-K is recommended to install a special polypropylene caps that protect against the ingress of dust and other elements that could contaminate the LED strip and impair its performance light.

The main advantages of the profile are its easy installation, low weight, good heat dissipation, and the fact that the profile is environmentally friendly.

We invite you to familiarize yourself with our offer.

Purpose:

- for LED lighting strips on soft or hard
- for lighting and illumination (depending on the power of applied LEDs)
- for indoor applications : to place in the channels (in slabs of furniture , cardboard plates - plaster wall surfaces)
- for outdoor use (the possibility of obtaining waterproof IP 67)

Product Description:

- Material : anodized aluminum
- Cover : frosted, transparent
- Standard lengths : 1m , 2m (we sell profiles odcinkach1 or 2 meter)
- Mounting: mounting adhesives , double-sided tape (accessories)
- Ending : Plastic plug (accessory)
- Certificate : CE
- Patent rights

Advantages :


small size allows for complete integration in the walls of the cabinet with small cross sections , a special collar allows you to hide unsightly edges of the channel (channel - specially prepared cavity in a plane plates , cardboard - gypsum walls, slabs , etc.) , easy installation , low weight , good heat emission , environment friendly


PDS4-K


PL / **Profil służy do konstruowania wbudowanych opraw oświetleniowych,** z kołnierzem zasłaniającym krawędzie wpustu.

EN / **The extrusion is used for construction of recessed light fixtures** with a flange covering the edges of the groove.


DE / **Das Profil dient zur Konstruierung der Einbauleuchten mir einem Flansch,** mit dem die Ränder des Falzes bedeckt werden.









LED 1 x 30cm: K-30-1275, 3000K
HS: REF.1369




LED 1 x 30cm: K-30-1275, 3000K
HS: REF.1370



LED: K-30-1275, 3000K
LIGER-v1 - REF.17037





PDS4-K

długość length Länge	szerokość paska LED LED strip width Breite LED Band	wykończenie powierzchni surface finish Oberfläche	numer artykułu article number Artikelnummer
1m (standard) 2m (standard) 3m (standard) 3 - 6m *	1 x LED strip max. 10,8 mm	anodowany / anodized / eloxiert	B3776ANODA
1m (standard) 2m (standard) 3m *	1 x LED strip max. 10,8 mm	czarny (anoda) / black (anodized) / schwarz (eloxiert)	B3776K7

* Na specjalne zamówienie / Special order / Sonderbestellung.

generated by the shopGold

OSŁONKI / COVERS / ABDECKUNGEN

	K	*łatwy montaż / easy to assemble / einfach zu montieren*	1m, 2m, 3m (standard)	PC	mleczna / frosted / opak	1547
					przezroczysta / transparent	1548
	KA-v1	*łatwy montaż / easy to assemble / einfach zu montieren*	1m, 2m, 3m (standard)	PC	mleczna / frosted / opak	17035
					przezroczysta / transparent	17036
	KA-BIS	*łatwy montaż, dobre rozpraszanie światła / easy to assemble, very good light dispersion / einfach zu montieren sehr gute Lichtstreuung*	1m, 2m, 3m (standard)	PC	mleczna / frosted / opak	17071
					przezroczysta / transparent	17072
	KA-COM	*łatwy montaż / easy to assemble / einfach zu montieren*	1m, 2m, 3m (standard)	PVC	mleczna / frosted / opak	17121
					przezroczysta / transparent	17122
	HS	*certyfikat UV, dobra klasa ognioodporności / UV certificate, good class of refractory – resistance / UV-Zertifikat, gute Feuerwiderstandsklasse*	1m, 2m, 3m (standard)	PC	mleczna / frosted / opak	1369
					przezroczysta / transparent	1370
	LIGER-v1	*doskonałe właściwości rozpraszające, wysoka jakość / excellent diffusing properties, high quality / Hervorragende diffundierende Eigenschaften, hohe Qualität*	1m, 2m, 3m (standard)	PC	mleczna / frosted / opak	17037

ZAŚLEPKI / END CAP / ENDKAPPEN

	PDS4-K	zaślepka podstawowa / basic end cap / Endkappe	PP		jasno szara / light gray / hellgrau	1438
			PP		metalizowana / metalised / metallisiert	24063
			PP		czarna / black / schwarz	24067
			PP		biała / white / weiss	20005
	PDS4-K	zaślepka z otworem / end cap with hole / Endkappe mit Kabelausgang	PP		jasno szara / light gray / hellgrau	1447
			PP		czarna / black / schwarz	24082
			PP		biała / white / weiss	21005

generated by the shopGold


PDS4-K




generated by the shopGold

PDS4-K







LINIA ŚWIATŁA

Za pomocą tego profilu można uzyskać linię światła. Szeroki kołnierz profilu pozwala na ukrycie nieestetycznych krawędzi kanału.

LIGHT LINE

A line of light may be obtained using this extrusion. The wide flange of the extrusion allows for hiding any unaesthetic edges of the groove.

LICHTLINIE


Mit diesem Profil kann man die Lichtlinie gewinnen. Der breite Flansch ermöglicht es, die unästhetischen Kanalränder zu bedecken.

generated by the shopGold


PDS 4 - K










22 mm
12 mm
16 mm