

Link to the product: <https://stair-lighting.com/profile-led-piko-o-white-ral9010-p-2780.html>

## Profile LED PIKO-O - white - RAL9010



Price	<b>6.75 Euro</b>
Availability	<b>Available</b>
Shipping time	<b>3 days</b>
Number	<b>2780</b>
Manufacturer	<b>KLUS</b>

### Product description

#### Important Information

The purchase a piece in the store means the purchase 1 linear meter of the profile or cover

If you want to buy a profile that has a length of 2 meters you have to buy 2 pieces, 3 meters you have to buy 3 pieces, and the multitude of quantity when ordering.

The total length of the aluminum profile or the panel to the profile - is the total quantity of the piece number that was bought in the store.

The choice of the appropriate shipping method will take place at the end of the order process.

[The details of the shipping method and packaging of the aluminum profiles you will find here \(click in the link\)](#)

The product you have selected contains only - aluminum profile - does not include the accessories located in the Accessories tab.

Additional accessories like covers, end caps, electricity conductive end cap, mounting bracket, fasteners, mounting springs, proximity switch, micro switch, mounting system and others are available under "Accessories".

If you are interested in longer lengths than one meter, write to us we will quote the delivery cost to you. Transport companies expect additional charges for long shipments.

For each country is different maximum length of the profile that we can send. It does not depend on us only by courier.

We also do service cutting aluminum profiles to the indicated size - write or call get comprehensive information.

Miniature external dimensions (outer diameter 10.5 mm)

Smooth exterior walls for a modern look

Easy bending of the profile

Narrow, subtle line of light

#### Application

General purpose profile.

#### Assembly

With conductive end caps.

#### Additional information

The lighting fixture is 360 degrees rotatable when coupled with PIKO-O conductive end caps

PIKO-O is compatible with 5 mm wide LED strips. The PIKO-O profile is available as silver anode and black anode.

Minimum internal bending radius: 150 mm.

Minimum external bending radius: 1000 mm.

Maximum deflection of the PIKO-O profile at a length of:

- 3 m is 45mm


- 2 m is 25 mm
- 1.75 m is 15 mm
- 1.50 m is 10 mm
- 1.20 m is 5 mm
- 1 m is 2 mm

The PIKO-O conductive end cap is designed for single-pole conductivity.  
The maximum forward current for the PIKO-O conductive end cap is 2 A.

Profile uniwersalne do montażu na powierzchni, wbudowania lub podwieszenia /  
Universalprofile zur Aufputz, Unterputzmontage oder zum Abhängen

## PIKO-O

REF. C1167



Miniaturowe gabaryty zewnętrzne (średnica zewnętrzna 10,5 mm).  
Gładkie ściany zewnętrzne zapewniają nowoczesną estetykę.  
Łatwe gięcie profilu.  
Wąska, subtelna linia światła.

#### PRZEZNACZENIE PRODUKTU:

- profil przeznaczony do ogólnego zastosowania.

#### MONTAŻ:

- za pomocą zaślepek przewodnikowych.

#### DODATKOWE INFORMACJE:

- możliwość obrotu oprawy 360 stopni przy pomocy zaślepek przewodnikowych PIKO-O,
- PIKO-O współpracuje z taśmami LED o szerokości 5 mm,
- gięcie profilu z osłoną LUK-10.



Sehr kleine Außenmaße (Außendurchmesser 10,5 mm).  
Glatte Außenwände sorgen für moderne Ästhetik.  
Einfaches Biegen des Profils.  
Schmale, subtile Lichtlinie.

#### ANWENDUNG

- Das Profil ist für den allgemeinen Gebrauch bestimmt

#### MONTAGE

- Mit Endkappen für Stromversorgung

#### ZUSÄTZLICHE INFORMATIONEN

- 360-Grad-Drehung der Leuchte mit PIKO-O Endkappen für Stromversorgung PIKO-O
- PIKO-O ist mit 5 mm breiten LED-Streifen kompatibel

#### profil / Profil

długość / Länge	szerokość LED / LED-Breite	wykończenie powierzchni / Oberfläche	numer artykułu / Artikelnummer
1 m	5 mm	● Srebrny anodowany / Silber eloxiert	<b>C1167ANODA_1</b>
2 m			<b>C1167ANODA_2</b>
3 m			<b>C1167ANODA_3</b>
1 m		● Czarny anodowany / Schwarz eloxiert	<b>C1167K7_1</b>
2 m			<b>C1167K7_2</b>
3 m			<b>C1167K7_3</b>


#### akcesoria / Zubehör

osłony mleczne / opale Abdeckungen	zaśleпки szare / graue Endkappen	zaśleпки czarne / schwarze Endkappen	zaśleпки przewodnikowe / leitende Endkappen
LUK-10 <b>17164</b>	PIKO-O <b>21234</b>	PIKO-O <b>24327</b>	PIKO-O <b>42631</b>

Universal Extrusions for surface mount, recessed or suspended applications /  
Perfiles universales para aplicaciones de montaje en superficie, empotradas o suspendidas

## PIKO-O

REF. C1167



Miniature external dimensions (outer diameter 0.41" / 10.5 mm).

Smooth exterior walls for a modern look.

Easy bending of the extrusion.

Narrow, subtle line of light.

### APPLICATION

- general purpose extrusion.

### ASSEMBLY

- with conductive end caps.

### ADDITIONAL INFORMATION

- the lighting fixture is 360 degrees rotatable when coupled with PIKO-O conductive end caps.
- PIKO-O is compatible with 0.19"/ 5 mm wide LED strips.
- extrusion bending with LUK-10 cover.



Tamaño exterior muy pequeño (diámetro exterior 0.41" / 10.5 mm).

Las paredes exteriores lisas garantizan una estética moderna.

Fácil curvado del perfil.

Haz de luz estrecho y sutil.

### APLICACIÓN

- general purpose extrusion.

### MONTAJE

- mediante tapas finales conductoras.

### INFORMACIÓN ADICIONAL

- posibilidad de girar la luminaria 360 grados con tapas finales conductoras PIKO-O.
- PIKO-O es compatible con tiras de LED de 0.19"/ 5 mm de ancho.
- El perfil PIKO-O tiene dos versiones de ánodo: plateado y negro.
- curvado del perfil con el difusor LUK-10.

### extrusion / perfil

length / longitud	space for LED strip / espacio para tira de LED	surface finish / terminado de superficie	reference number / número de artículo
39.4" / 1 m	0.19"/ 5 mm	● Silver anodized / Ánodo de plata	C1167ANODA_1
78.7" / 2 m			C1167ANODA_2
118" / 3 m			C1167ANODA_3
39.4" / 1 m		● Black anodized / Negro anodizado	C1167K7_1
78.7" / 2 m			C1167K7_2
118" / 3 m			C1167K7_3

### accessories / accesorios

frosted covers / difusores escarchados	grey end caps / tapas finales gris	black end caps / tapas finales negro	electricity conductive end caps/ tapas finales conductora de electricidad
LUK-10 17164	PIKO-O 24321	PIKO-O 24327	PIKO-O 42631



