

Link to the product: <https://stair-lighting.com/profile-led-te-4-p-1729.html>

Profile LED TE-4

Price	18.78 Euro
Availability	Goods are unavailable
Shipping time	4 days
Number	1729
Manufacturer	KLUS

Product description

Important Information

The purchase a piece in the store means the purchase 1 linear meter of the profile or cover

If you want to buy a profile that has a length of 2 meters you have to buy 2 pieces, 3 meters you have to buy 3 pieces, and the multitude of quantity when ordering.

The total length of the aluminum profile or the panel to the profile - is the total quantity of the piece number that was bought in the store.

The choice of the appropriate shipping method will take place at the end of the order process.

[The details of the shipping method and packaging of the aluminum profiles you will find here \(click in the link\)](#)

Aluminum profile

The product you have selected contains only - aluminum profile - does not include the accessories located in the Accessories tab.

Additional accessories like covers, end caps, electricity conductive end cap, mounting bracket, fasteners, mounting springs, proximity switch, micro switch, mounting system and others are available under "Accessories".

If you are interested in longer lengths than one meter, write to us we will quote the delivery cost to you. Transport companies expect additional charges for long shipments.

For each country is different maximum length of the profile that we can send. It does not depend on us only by courier.

We also do service cutting aluminum profiles to the indicated size - write or call get comprehensive information.

TE-profile 4 is used in the construction of precise and careful slots (so-called. Inlets) in the planes of the walls, ceilings and cardboard - gypsum, which are then deposited lighting fixtures made of profiles PDS4-ALU and PDS4-K.

The wide flange profile which is characterized by TE-4 is dedicated to the standard coating materials that are used to connect, as well as any finishing of the surface area of drywall - gypsum.

Mounting profiles is very simple and easy to carry. Profile PDS4-ALU and PDS4-K is mounted on the so-called. "Interference", thus enabling easy installation of all kinds of lighting fixtures, as well as their disassembly for maintenance, which is not associated with injuries.

A convenient place to the rear profile of TE-4 are slots previously installed drywall - gypsum. Usually it is fixed with glue gypsum (GS 20 CECOL or similar) or mounting. It should be remembered that when the glue is dry aluminum flanges should be clad with a thin layer of specially designed for this purpose glue, then put on a reinforcing mesh and fill all whole.

After the interval, in which the adhesive is dry it is advisable to carefully sand the putty to the edges of the profile has become



